

**DAC-206**

# Wear Guard 2000 Lubricant



## Why was Wear Guard 2000 developed?

Our customers expressed a desire for a complete family of lubrication and anti-wear products that will perform over a wide range of operating temperatures under varying conditions.

Wear Guard 2000 was formulated to provide optimum lubrication and anti-wear for medium operating temperatures of 0°F to +600°F.

## DESCRIPTION:

Wear Guard 2000 is an anti-wear and lubrication package for medium temperature molding requirements. Wear Guard 2000 eliminates the high cost of expensive plating agents. Wear Guard 2000 should be used on all moving parts, slides, cams, and pins where galling may occur.

## PERFORMANCE CHARACTERISTICS:

- Superior film strength protects against galling and binding
- Eliminates all chance of bleeding through ejectors, cams and lifters
- Excellent product for temperatures 0°F to 600°F
- Superior film strength
- Excellent lubrication
- Anti-wear protection
- User friendly
- No bleeding
- Dry film

## CAUTION:

To maintain peak film strength performance, do not use in conjunction with any mineral oil or lithium based products. Use in well-ventilated area. Store at room temperatures below 120°F.

### NPCA Hazardous Materials ID System

Health	1
Flammability	4
Reactivity	0
Personal Protection	*

©2004 DAC Industries, Inc. All Rights Reserved

Call for Orders, Product Information and Technical Support:

**1-800-830-3423**



DAC Industries, Inc.  
1730 Gervais Avenue East  
Maplewood, MN 55109 USA

tel: 1-651-748-1750  
fax: 1-651-748-1748  
info@moldsprays.com  
www.moldsprays.com