

## **DIECO Die Makers Grease**

- Lithium Complex
- Fortified with extreme pressure additives
- Excellent for close tolerance, high unit pressure applications
- Dropping point of 500°F, Freeze point of 10°F
- Rust and oxidation inhibitors added
- Ideal for use with Die Sets on Pins and Bushings

DIECO Part #	Description
40-1001	1/2 lb. Tube
40-1003	14 oz. Cartridge
40-1002	35 lb. Pail



## Huskey Hi-Lo ISO 100 (formerly DIECO Linear Lube)

- Same product, new package
- Designed for use on ball bearing assemblies
- Blend of the finest quality pure synthetic oils available
- USDA H-1 rated. Full acceptability for use in all areas where incidental food contact may occur

DIECO Part #	Description
42-1022	Gallon

## **DIECO Pry Bars & Bronze Tips**

- PRY BARS Made of hexagonal high carbon steel stock, hot forged to shape and cadmium plated
- Weighs only 1 3/4 lbs. with an overall length of 18 3/4"
- BRONZE TIPS Available to fit on curved ends of pry bars and are removable

DIECO Part #	Description
41-1025	18" Pry Bar
41-1026	Bronze Cast Tip



## **Ostalloy**

- Fusible Alloys are low melting temperature compositions containing bismuth, lead, tin, cadmium or indium
- Only expands approximately 3.3% of their volume when changing from molten to solid form
- Advantage of fusible alloys is their capacity for recovery
- · Can be remelted and used again and again
- Ideal for many industrial applications including casting, tube bending, machining parts for soft metal dies, fixturing, soft metal casting, joggle dies and supporting castings and interrupted cuts
- Sold in 1 pound increments

DIECO Part #	Description
OST117	OSTALLOY 117
OST136	OSTALLOY 136
OST158	OSTALLOY 158
OST160-190	OSTALLOY 160-190

dieco <b>Part #</b>	Description
OST217-440	OSTALLOY 217-440
OST255	OSTALLOY 255
OST281	OSTALLOY 281
OST281-338	OSTALLOY 281-338

Number indicates melting temperature

